

ZWS5036/J Information

Heisener.com

Part Number ZWS5036/J

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 36V 50W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS5036/J Specifications

Manufacturer Part Number ZWS5036/J Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer Part Number	ZWS5036/J
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Series	ZWS
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.4A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 36V - Size / Dimension 36V - 3	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension Chassis Mount 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sifficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Output A - Output Capable, Universal Input - Output A - Output A - Output A - Output Capable, Universal Input - Output A	Voltage - Output 1	36V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 3	-
Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Current - Output (Max)	1.4A
Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Power (Watts)	50W
Efficiency 82% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Efficiency	82%
Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Operating Temperature	-10°C ~ 60°C (With Derating)
Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)
		Report errors?

ZWS5036/J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS5036/J Payment Methods



















ZWS5036/J Shipping Methods













If you have any question about ZWS5036/J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com