

## **ZWS5048/J Information**

Heisener.com

Part Number ZWS5048/J

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

**AC DC Converters** 

**Description** AC/DC CONVERTER 48V 50W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ZWS5048/J Specifications**

Manufacturer Part Number         ZWS5048/J           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ZWS           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer Part Number	ZWS5048/J
Package         -           Series         ZWS           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         ZWS           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         ZWS           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Series	ZWS
Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         48V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         -           Power (Watts)         50W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         82%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, DC Input Capable, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Туре	Open Frame
Voltage - Output 1 48V  Voltage - Output 2 -  Voltage - Output 3 -  Voltage - Output 4 -  Current - Output (Max) -  Power (Watts) 50W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 82%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  82%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 1	48V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  82%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  82%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 3	-
Power (Watts) 50W  Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 82%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 3kV (3000V)  Efficiency 82%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Current - Output (Max)	-
Voltage - Isolation 3kV (3000V)  Efficiency 82%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Power (Watts)	50W
Efficiency 82%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Applications	ITE (Commercial)
Operating Temperature  -10°C ~ 60°C (With Derating)  Adjustable Output, DC Input Capable, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Efficiency	82%
Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Features	Adjustable Output, DC Input Capable, Universal Input
· · · · · · · · · · · · · · · · · · ·	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)
		Report errors?

### **ZWS5048/J Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ZWS5048/J Payment Methods**



















## **ZWS5048/J Shipping Methods**













If you have any question about ZWS5048/J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com