



ZWS50AF5 Information

Heisener.com

Part Number ZWS50AF5

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 5V 50W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS50AF5 Specifications

Manufacturer Part Number ZWS50AF5 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 768" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer Part Number	ZWS50AF5
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Series	ZWS
Voltage - Input85 ~ 265 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)50WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency75%Operating Temperature-10°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Type	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Site / Dimension 5V 5V Applications TE (With Derating) Chassis Mount Tourent - Output (Max) 5V Tourent - Output (Max) Features Adjustable Output, DC Input Capable, Universal Input Tourent - Output (Max) Tourent - Output (Max) Features Adjustable Output, DC Input Capable, Universal Input Tourent - Output Tour	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 3	-
Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	10A
Voltage - Isolation 3kV (3000V) Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Power (Watts)	50W
Efficiency 75% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Applications	ITE (Commercial)
Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Efficiency	75%
Mounting Type Chassis Mount Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Operating Temperature	-10° C ~ 60° C (With Derating)
Size / Dimension 7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 2.17" W x 1.02" H (195.0mm x 55.1mm x 25.9mm)
Report errors.		Report errors?

ZWS50AF5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS50AF5 Payment Methods



















ZWS50AF5 Shipping Methods













If you have any question about ZWS50AF5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com