

ZWS524 Information

Part Number ZWS524

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 5W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZWS524 Specifications

Manufacturer Part Number ZWS524 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	*		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Manufacturer Part Number	ZWS524	
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ZWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Package	-	
Number of Outputs1Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)220mAPower (Watts)5WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency68%Operating Temperature-10°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Series	ZWS	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 220mA Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Type	Open Frame	
Voltage - Output 2 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 24V 24V 24V 24V 24V 24V 24V 25V 26 27 28 28 28 29 29 20 20 20 20 20 20 20 20	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sifficiency Operating Temperature Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Current -	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Voltage - Output 3	-	
Power (Watts) 5W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Voltage - Output 4	-	
ApplicationsITE (Commercial)Voltage - Isolation $3kV (3000V)$ Efficiency 68% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, DC Input Capable, Load Sharing, PFC, Universal InputMounting TypeChassis MountSize / Dimension 3.86 " L x 1.77 " W x 0.83 " H $(98.0 \text{mm} \times 44.9 \text{mm} \times 21.0 \text{mm})$	Current - Output (Max)	220mA	
Voltage - Isolation 3kV (3000V) Efficiency 68% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Power (Watts)	5W	
Efficiency 68% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount 3.86 " L x 1.77 " W x 0.83 " H $(98.0 \text{mm} \times 44.9 \text{mm} \times 21.0 \text{mm})$	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Efficiency	68%	
Mounting Type Chassis Mount Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Operating Temperature	-10° C ~ 60° C (With Derating)	
Size / Dimension 3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	Features	Adjustable Output, DC Input Capable, Load Sharing, PFC, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	3.86" L x 1.77" W x 0.83" H (98.0mm x 44.9mm x 21.0mm)	
			Report errors?

ZWS524 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZWS524 Payment Methods



















ZWS524 Shipping Methods













If you have any question about ZWS524, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com