



ZXRE1004CFTC Information



For Reference Only

Part Number ZXRE1004CFTC

Manufacturer Diodes Incorporated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

DescriptionIC VREF SHUNT 1.22V SOT23PackageTO-236-3, SC-59, SOT-23-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ZXRE1004CFTC Specifications

Manufacturer Part Number ZXRE1004CFTC Manufacturer Diodes Incorporated Category Integrated Circuits (ICs) Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.22V Voltage - Output (Max) - Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10Hz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.22V Voltage - Output (Max) - Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Manufacturer Part Number	ZXRE1004CFTC
Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.22 V Voltage - Output (Max) - Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Manufacturer	Diodes Incorporated
Package TO-236-3, SC-59, SOT-23-3 Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.22V Voltage - Output (Max) - Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75pm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Category	Integrated Circuits (ICs)
Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 1.22 V Voltage - Output (Max) - Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23		PMIC - Voltage Reference
Reference TypeShuntOutput TypeFixedVoltage - Output (Min/Fixed)1.22VVoltage - Output (Max)-Current - Output20mATolerance±0.5%Temperature Coefficient75ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz60μVrmsVoltage - Input-Current - Supply-Current - Cathode8μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Package	TO-236-3, SC-59, SOT-23-3
Output TypeFixedVoltage - Output (Min/Fixed)1.22VVoltage - Output (Max)-Current - Output20mATolerance±0.5%Temperature Coefficient75ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz60μVrmsVoltage - Input-Current - Supply-Current - Cathode8μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Series	-
Voltage - Output (Min/Fixed) Voltage - Output (Max) Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply Current - Cathode 0perating Temperature 40°C ~ 85°C (TA) Mounting Type Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Reference Type	Shunt
Voltage - Output (Max)-Current - Output20mATolerance±0.5%Temperature Coefficient75ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz60μVrmsVoltage - Input-Current - Supply-Current - Cathode8μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Output Type	Fixed
Current - Output 20mA Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Voltage - Output (Min/Fixed)	1.22V
Tolerance ±0.5% Temperature Coefficient 75ppm/°C Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 60μVrms Voltage - Input - Current - Supply - Current - Cathode 8μA Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package	Current - Output	20mA
Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz $60\mu Vrms$ Voltage - Input-Current - Supply-Current - Cathode $8\mu A$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Tolerance	±0.5%
Noise - 10Hz to 10kHz $60\mu Vrms$ $-$ Current - Supply $-$ Current - Cathode $8\mu A$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA) Mounting Type Surface Mount Package / Case $TO-236-3$, SC-59, SOT-23-3 Supplier Device Package	Temperature Coefficient	75ppm/°C
Voltage - Input-Current - Supply-Current - Cathode $8μA$ Operating Temperature $-40°C ~ 85°C (TA)$ Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Noise - 0.1Hz to 10Hz	-
Current - Supply-Current - Cathode8μAOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Noise - 10Hz to 10kHz	$60\mu Vrms$
Current - Cathode $8\mu A$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Voltage - Input	-
Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Current - Supply	-
Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Current - Cathode	8μΑ
Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Operating Temperature	-40°C ~ 85°C (TA)
Supplier Device Package SOT-23	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Report errors?	Supplier Device Package	SOT-23
		Report errors?

ZXRE1004CFTC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ZXRE1004CFTC Payment Methods





















ZXRE1004CFTC Shipping Methods













If you have any question about ZXRE1004CFTC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com